

SWIFT EQUIPMENT

SWIFT 0812L

26FT ELECTRIC SCISSOR LIFT WITH OUTRIGGERS

The Swift 0812L offers exceptionally durable performance, and superior productivity. Swift Scissor Lifts are a great choice for your EWP solutions and are noiseless, versatile and environmentally friendly. Suitable for commercial indoor or outdoor commercial or private applications. With inbuilt stabilisers, the 0812L is perfect for those uneven surfaces



460kg Lift capacity



Perfect for outdoor use



Auto levelling with stabilisers - 10°



Compact and narrow



Easily transportable/towable



Noiseless & Eco friendly



Scan for images,
videos & pricing



1300 477 055



sales@swiftequipment.com.au



www.swiftequipment.com.au

Head Office 📍 41 Southeast Blvd, Pakenham, VIC 3810

Dimensions

Max. Working Height 9.9m

Max. Platform Height 7.9m

Overall Length (Stowed) 2.72m

Overall Width 1.18m

Overall Height (Guardrails unfolded) 2.31m

Overall Height (Guardrails folded) 1.80m

Platform Length (Stowed) 2.25m

Max Horizontal Reach (Extension) 0.9m

Platform Width 1.16m

Wheelbase 1.85m

Ground Clearance (Stowed) 0.1m

Ground Clearance (Lifting) 0.02m

Weight

Overall Weight 2706kg

Performance

Max. Platform Occupancy (In door) 2

Max. Platform Occupancy (Out door) 1

Lift Capacity 460kg

Lift Capacity (Extension deck) 120kg

Driving Height Full height

Driving speed (Stowed) 0-3.2 km/h

Driving speed (Raised) 0-0.8 km/h

Gradeability 0.3

Turning Radius (Inside) 0

Turning Radius (Outside) 2.45 m

Maximum Working Inclination Angle 1.5°/3°

Rise/Lower Speed 30/30 sec.

Track Tyre 38*13 cm

SWIFT EQUIPMENT

BRANCHES

BRISBANE - SYDNEY - ADELAIDE



1300 477 055



sales@swiftequipment.com.au



www.swiftequipment.com.au

Head Office 📍 41 Southeast Blvd, Pakenham, VIC 3810