

XG0607DC

SCISSOR LIFTS


FEATURES

PRODUCTIVITY

- 2 rear driving wheels
- 25% theoretical gradeability-stowed/lowered position
- Battery charge indicator and diagnostic display for faults
- Manual platform lowering valve
- Both platform and ground control panel with emergency stop button
- Rear wheel multi-disc brakes
- Manual brake release system
- Solid non-marking tires
- Mobile pothole protection
- Tilt alarm
- Hourmeter screen
- Lift and lower alarm
- Horn
- Dual flashing beacons
- Drive alarm
- Overload alarm

OPTIONS

- Platform working light
- Air-line to platform
- AC power to the platform



Item	Unit	XG0607DC
Lift capacity	kg	240
Lift capacity of extended platform	kg	100
Occupant Capacity	-	2
Working height	m	5.9
Platform height	m	3.9
a Length(no ladder)	mm	1440(1290)
b Width	mm	760
c Height(platform folded)	mm	2020(1660)
d × e Platform size(Length × Width)	mm	1290 × 700
Extended platform size(Length × Width)	mm	600
Ground clearance(pil protector rising/descending)	mm	65/15
f Wheelbase	mm	1030
Turning radius(inner/outer wheel)	m	0.4/1.55
Drive motor	kW	0.45
Lift motor	kW	1.3
Drive speed at low level	km/h	4.0
Drive speed at high level	km/h	0.5
Lift/Lower time	s	27 ~ 37/23 ~ 33
Gradeability	%	25
Tilt alarm(side/forward and backward)	°	1.5/3
Batteries	V/Ah	2 × 12/85(2 × 12/75)
Charger	V/A	24/15
Tires	-	254 × 76
Weight	kg	900